

SIMATIC S7-300, ANALOG OUTPUT SM 332, OPTICALLY ISOLATED, 4 AO, U/I; DIAGNOSTICS; RESOLUTION 11/12 BITS, 20 PIN, REMOVE/INSERT W. ACTIVE, BACKPLANE BUS



Figure similar

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	240 mA
from backplane bus 5 V DC, max.	60 mA
Power loss	
Power loss, typ.	3 W
Analog outputs	
Number of analog outputs	4
Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	25 mA
Current output, no-load voltage, max.	18 V
Output ranges, voltage	
• 0 to 10 V	Yes
• 1 V to 5 V	Yes

• -10 V to +10 V	Yes
<b>Output ranges, current</b>	
• 0 to 20 mA	Yes
• -20 mA to +20 mA	Yes
• 4 mA to 20 mA	Yes
<b>Load impedance (in rated range of output)</b>	
• with voltage outputs, min.	1 k $\Omega$
• with voltage outputs, capacitive load, max.	1 $\mu$ F
• with current outputs, max.	500 $\Omega$
• with current outputs, inductive load, max.	10 mH
<b>Cable length</b>	
• shielded, max.	200 m
<b>Analog value generation</b>	
<b>Integration and conversion time/resolution per channel</b>	
• Resolution with overrange (bit including sign), max.	12 bit; $\pm$ 10 V, $\pm$ 20 mA, 4 mA to 20 mA, 1 V to 5 V: 11 bit + sign; 0 V to 10 V, 0 mA to 20 mA: 12 bit
• Conversion time (per channel)	0.8 ms
<b>Settling time</b>	
• for resistive load	0.2 ms
• for capacitive load	3.3 ms
• for inductive load	0.5 ms; 0.5 ms (1 mH); 3.3 ms (10 mH)
<b>Errors/accuracies</b>	
<b>Operational error limit in overall temperature range</b>	
• Voltage, relative to output area, (+/-)	0.5 %
• Current, relative to output area, (+/-)	0.6 %
<b>Basic error limit (operational limit at 25 °C)</b>	
• Voltage, relative to output area, (+/-)	0.4 %
• Current, relative to output area, (+/-)	0.5 %
<b>Interrupts/diagnostics/status information</b>	
Diagnostic functions	Yes; Parameterizable
Substitute values connectable	Yes; Parameterizable
<b>Alarms</b>	
• Diagnostic alarm	Yes; Parameterizable
<b>Diagnostic messages</b>	
• Diagnostic information readable	Yes
<b>Diagnostics indication LED</b>	
• Group error SF (red)	Yes
<b>Potential separation</b>	
<b>Potential separation analog outputs</b>	
• between the channels and backplane bus	Yes

### Isolation

Isolation tested with	500 V DC
-----------------------	----------

### Connection method

required front connector	20-pin
--------------------------	--------

### Dimensions

Width	40 mm
-------	-------

Height	125 mm
--------	--------

Depth	117 mm
-------	--------

### Weights

Weight, approx.	220 g
-----------------	-------

<b>last modified:</b>	18.12.2015
-----------------------	------------