

SIMATIC S7-1500, DIGITAL OUTPUT MODULE, DQ 16 X
24VDC/0.5A; 16 CHANNELS IN GROUPS OF 8, 4 A PER GROUP;
INCL. FRONT CONNECTOR PUSH-IN



| General information | |
|---|---------------------------|
| Product type designation | DQ 16x 24 V DC / 0.5 A BA |
| HW functional status | FS01 |
| Firmware version | V1.0.0 |
| <ul style="list-style-type: none"> FW update possible | Yes |
| Product function | |
| <ul style="list-style-type: none"> I&M data | Yes; I&M0 to I&M3 |
| Engineering with | |
| <ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated as of version | V13 / V13 |
| <ul style="list-style-type: none"> STEP 7 configurable/integrated as of version | V5.5 SP3 / - |
| <ul style="list-style-type: none"> PROFIBUS as of GSD version/GSD revision | V1.0 / V5.1 |
| <ul style="list-style-type: none"> PROFINET as of GSD version/GSD revision | V2.3 / - |
| Operating mode | |
| <ul style="list-style-type: none"> DQ | Yes |
| <ul style="list-style-type: none"> DQ with energy-saving function | No |
| <ul style="list-style-type: none"> PWM | No |
| <ul style="list-style-type: none"> Oversampling | No |
| <ul style="list-style-type: none"> MSO | Yes |

| Supply voltage | |
|---|---|
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 20.4 V |
| permissible range, upper limit (DC) | 28.8 V |
| Reverse polarity protection | Yes; through internal protection with 7 A per group |
| Input current | |
| Current consumption, max. | 30 mA |
| Output voltage | |
| Rated value (DC) | 24 V |
| Power | |
| Power available from the backplane bus | 1.15 W |
| Power loss | |
| Power loss, typ. | 2.2 W |
| Digital outputs | |
| Number of digital outputs | 16 |
| Current-sourcing | Yes |
| Short-circuit protection | Yes |
| • Response threshold, typ. | 1 A |
| Limitation of inductive shutdown voltage to | L+ (-53 V) |
| Controlling a digital input | Yes |
| Switching capacity of the outputs | |
| • with resistive load, max. | 0.5 A |
| • on lamp load, max. | 5 W |
| Load resistance range | |
| • lower limit | 48 Ω |
| • upper limit | 12 k Ω |
| Output voltage | |
| • for signal "1", min. | L+ (-0.8 V) |
| Output current | |
| • for signal "1" rated value | 0.5 A |
| • for signal "1" permissible range, max. | 0.5 A |
| • for signal "0" residual current, max. | 0.5 mA |
| Output delay with resistive load | |
| • "0" to "1", max. | 100 μ s |
| • "1" to "0", max. | 500 μ s |
| Parallel switching of two outputs | |
| • for logic links | Yes |
| • for uprating | No |
| • for redundant control of a load | Yes |
| Switching frequency | |

| | |
|--|---|
| <ul style="list-style-type: none"> • with resistive load, max. | 100 Hz |
| <ul style="list-style-type: none"> • with inductive load, max. | 0.5 Hz; According to IEC 60947-5-1, DC-13 |
| <ul style="list-style-type: none"> • on lamp load, max. | 10 Hz |
| Total current of the outputs | |
| <ul style="list-style-type: none"> • Current per channel, max. | 0.5 A; see additional description in the manual |
| <ul style="list-style-type: none"> • Current per group, max. | 4 A; see additional description in the manual |
| <ul style="list-style-type: none"> • Current per module, max. | 8 A; see additional description in the manual |
| Cable length | |
| <ul style="list-style-type: none"> • shielded, max. | 1 000 m |
| <ul style="list-style-type: none"> • unshielded, max. | 600 m |
| Isochronous mode | |
| Isochronous operation (application synchronized up to terminal) | No |
| Interrupts/diagnostics/status information | |
| Diagnostics | No |
| Substitute values connectable | No |
| Alarms | |
| <ul style="list-style-type: none"> • Diagnostic alarm | No |
| Diagnostic messages | |
| <ul style="list-style-type: none"> • Monitoring the supply voltage | No |
| <ul style="list-style-type: none"> • Wire-break | No |
| <ul style="list-style-type: none"> • Short-circuit | No |
| <ul style="list-style-type: none"> • Group error | No |
| Diagnostics indication LED | |
| <ul style="list-style-type: none"> • RUN LED | Yes; Green LED |
| <ul style="list-style-type: none"> • ERROR LED | Yes; Red LED |
| <ul style="list-style-type: none"> • Monitoring of the supply voltage (PWR-LED) | Yes; Green LED |
| <ul style="list-style-type: none"> • Channel status display | Yes; Green LED |
| <ul style="list-style-type: none"> • for channel diagnostics | No |
| <ul style="list-style-type: none"> • for module diagnostics | No |
| Potential separation | |
| Potential separation channels | |
| <ul style="list-style-type: none"> • between the channels | No |
| <ul style="list-style-type: none"> • between the channels, in groups of | 8 |
| <ul style="list-style-type: none"> • between the channels and backplane bus | Yes |
| Isolation | |
| Isolation tested with | 707 V DC (type test) |
| Decentralized operation | |
| Prioritized startup | Yes |
| Dimensions | |

| | |
|--------|--------|
| Width | 25 mm |
| Height | 147 mm |
| Depth | 129 mm |

Weights

| | |
|-----------------|-------|
| Weight, approx. | 230 g |
|-----------------|-------|

Other

Note: Supplied incl. 40-pole push-in front connectors

last modified: 09.04.2016